



LOFT

Think Bigger!


Equipped with a lift & slide mechanism that opens oversized glass panels with ease, Loft merges indoor and outdoor environments seamlessly. Safe, durable, maintenance-free and efficient, Loft will redefine your living space.

Loft lift & slide patio door, 10' x 8' (3.02 m x 2.42 m) black with brushed chrome handle.

Loft Patio Door


✕ OPERATING PANEL ○ FIXED PANEL (OUTSIDE VIEW)

6' WIDTH




71½" × 79½"
70½" × 81"
71½" × 95½"
71½" × 107½"

8' WIDTH




95½" × 79½"
94½" × 81"
95½" × 95½"
95½" × 107½"

9' WIDTH



107" × 79½"
107" × 81"
107" × 95½"
107" × 107½"


10 & 12' WIDTH



119" × 79½"
119" × 81"
119" × 95½"
119" × 107½"
143" × 79½"
143" × 81"
143" × 95½"


ASYMMETRICAL CONFIGURATION — AVAILABLE LEFT- OR RIGHT-HANDED

7' WIDTH




83⅞" × 79½"
82½" × 81"
83⅞" × 95½"
83⅞" × 107½"

8' WIDTH




95¼" × 79½"
94¾" × 81"
95¼" × 95½"
95¼" × 107½"

9' WIDTH



107⅝" × 79½"
106¾" × 81"
107⅝" × 95½"
107⅝" × 107½"

10' WIDTH



119⅝" × 79½"
118⅞" × 81"
119⅝" × 95½"
119⅝" × 107½"



Lift & Slide

Loft's contemporary-style handle pivots to release the three-point locking mechanism and raise the door weighing up to 300 lb | 136 kg!




Flow lift & slide handle ^{NEW}

- White
- Black
- Satin Chrome

Frame and Sash Color

Any combination of these colors on the inside and outside of the frame and sash is possible.



White (K-1285)



Black (K-90421)



Clear Anodized (Option)



Custom Color (Option)

Specifications

Materials: Lift & slide aluminum patio door with polyamide thermal break.

Frame Depth: 6", 7¼", 8" or 9¼"

Glazing:

1" double glazed — Low-E on surface 3
U-value: 1.87/0.33, SHGC 0.57, ER 32

1" double glazed — Low-E on surface 2 (Option)
U-value: 1.82/0.32, SHGC 0.30, ER 17

1¼" triple glazed — Low-E on surface 5 (Option)*
U-value: 1.48/0.26, SHGC 0.51, ER 37 CAN

1¼" triple glazed — Low-E on surface 2 (Option)*
U-value: 1.48/0.26, SHGC 0.19, ER 19 CAN/US all zones

1" double glazed — Low-E on surface 2 & 4 (Option)
U-value: 1.59/0.28, SHGC 0.20, ER 17 US South et South Central

Sill Color



Clear Anodized outside / inside



Black anodized outside / clear inside



Black anodized outside / inside

Standard

- Anodized aluminum threshold cover
- Triple-point locking system

Options

- Sidelites and transoms
- Grilles*
- Ultra-resistant Robusto screen**
- Aluminum sill extension
- Aluminum brick mould
- Aluminum drywall return
- Nailing fin

* Options only available for some door configurations.

** Heavy-duty screen standard on large doors.

Performance Air: A3 Water: 360 Pa / 7.5 psf Global: LC-PG40 without reinforcement, CW-PG50 with reinforcement (Option) STC: up to 37
Door: 95½" × 95½" (OX/XO) (AAMA/WDMA/CSA101/I.S.2/A440-11)

20-Year Limited Warranty See the detailed warranty on our website.